











Competition ZERO3 for Suzuki Swift Sport(ZC31S) has been released







♦ Major specifications

•24 steps adjustable damping, needle valve type, Overall length system adjustment, Upper mount less

♦ It's applied Mono-tube shock absorber with large calibre piston which is suitable for proper circuit driving or long distance sporty driving. needle valve type 24 steps damping force adjustable system cope to detailed setting for competition driving. This is the sport coil over kit for the competition which is on battle of hundredths of a second.

♦It copes to wide range of condition by setting which is designed to bring stable controllability of Swift Sport out.

♦ Camber is adjustable by fitting hole of the front knuckle bracket from approx.-1 to -4(*1). With adjust to negative camber, front grip on cornering will be improved which brings better time on circuit.

Applicable model		Part No.	Price(excl.tax)	Height adjustable		SP rate		U/M	Height adjust	D.O.R.
Suzuki Swift	ZC31S	616 63R CB	£2,040.79	F	-45∼ 0mm	F	12k(*2)	-	Overall length	l 29 July I
				R	-55∼-20mm	R	10k(*2)	-	Threaded spacer	

^{*1} The data based of our test car. The rate could be different depend on the height or individual character.

*U/M=Upper mount, - = no including





^{*2} the spring rate change is available with no charge at ordering. For Swift, choose the rate from F:8,9,10,11,14,16k/R:7,8,9,12,14k.